

Drum Storage Shelters Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>
21000mm	2500mm	1900mm

Front Options Available:

<u>Options:</u>
Single Gated Open Fronted Shelter
Double Gated Open Fronted Shelter
Single Gated Mesh Infill Door Shelter
Double Gated Mesh Infill Door Shelter
Single Gated Galvanised Panel Fronted Shelter
Double Gated Galvanised Panel Fronted Shelter

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800

Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com

Drum Shelter Construction:


- Various options of door fronts, from steel, mesh or galvanised panels.
- Adjustable feet for on-site positioning.
- Para-bolts for surface mounting included. Must be bolted to 250mm thick concrete for stability.
- Available in various framework colour options.
- Manufactured from heavy duty box mild steel.
- Internal storage area is 2.35 wide x 2.1 high x 1.37 metres deep.
-

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Drum Shelter available with various powder coated framework colour options

Drum Shelter Colours:

Blue	RAL 5017
Green	RAL 6028
Light Grey	RAL 7035



Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800

Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com