

G-TEK® HYDRUS® GF360,15 GAUGE SEAMLESS KNITTED GLOVE, NYLON LINER, FULL HAND FLAT NITRILE COATING WITH G2 FOAM NITRILE ON PALM AND FINGERS , OEKO TEX MADE IN GREEN.

- Constructed using a 15gg nylon liner and a dual-layer nitrile coating system, the Hydrus® range provides the user with unrivalled oil and liquid resistance whilst maximising comfort, dexterity, and grip from the very first use.
- Comprising an initial 360-degree flat nitrile layer to deliver liquid and oil resistance, this unique dipping style provides full protection right up to the end of the cuff without compromising fit, dexterity, or comfort. Overlaid with an additional palm coating in next-generation G² nitrile foam, grip and longevity are maximised in all environments and, during in-house testing, performance exceeded that of regular sandy or microfoam nitrile coatings, as well as traditional PU and latex options.
- The 26 cm length offers extra protection to the wrist area and prevents both dirt and liquid ingress.
- Both OEKO-TEX® Standard 100 and OEKO-TEX® MADE IN GREEN certified, the Hydrus® range is tested for harmful substances and produced in environmentally friendly and socially responsible facilities.
- Contact heat Level 1 tested for temperatures up to 100 °C.

APPLICATIONS

- Light manufacturing
- Logistics
- Equipment servicing

CARE INSTRUCTIONS

The gloves can be machine washed at 40°C with a standard detergent (3 wash cycles). Air dry. This helps extend the glove's lifespan and reduce costs and waste.

TECHNICAL SPECIFICATIONS

MATERIAL	Liner : Nylon Full hand flat nitrile coating, G2 foam nitrile on palm & fingers
CONSTRUCTION	Seamless knit
COLOUR	Liner: ■ Black ■ Red / Coating ■ Black ■ Red
WRIST STYLE	Knit wrist
SIZES	7 - 11
PACKAGE	12 pairs per bag, 120 pairs per case.
COO	China

PERFORMANCE PROPERTIES

EN388: 4121A							
ABRASION	0	1	2	3	4	-	-
CUT (2003)	0	1	2	3	4	5	X
TEARING	0	1	2	3	4	-	-
PUNCTURE	0	1	2	3	4	-	-
CUT (ISO 13997)	A	B	C	D	E	F	X



DIMENSIONS (IN/CM)

	7	8	9	10	11
A	10.2 / 26	10.2 / 26	10.2 / 26	10.2 / 26	10.2 / 26
B	3.4 / 8.8	3.7 / 9.5	3.8 / 9.8	4 / 10.2	4.2 / 10.8

